

*Materials of Conferences*

**INSTALLATION FOR OIL-WATER  
EMULSION FUELS PRODUCTION FROM  
ORGANIC WASTES, CONTROLLED  
BY NUCLEAR MAGNETIC RESONANCE  
RELAXOMETER**

Faschiev N.R., Kashaev R.S.-H  
Kazan State Power Engineering University,  
Kazan, Republic Tatarstan. Russian Federation  
[kashaev2007@yandex.ru](mailto:kashaev2007@yandex.ru)

Problem of organic waste utilization and search for new alternative fuels is actual now. The authors propose to convert oil components of the organic/water waste in fuel emulsions (fuemulsions) with water content up to 20-30 %. Use of fuemulsions (for example bitumen/water emulsions) give advantages: practically complete combustion and conversion of carbon due to water drops bursts in flame; opportunity for combustion at oxygen lack; low temperature of the burner flame and hence decrease in orders of atmosphere waste by polyaromatic chance gene compounds and decrease on 65-80 % of nitrogen oxides NOX; concentration of the ash after combustion of the fuemulsions in 100 time lower, then from coal and the ash can be used as an ore for metals V and Ni, concentrations of which are 260 mg/kg and 55 mg/kg.

Used method for water decrease and hydrocarbon extraction from waste water - is treatment in rotating magnetic and nonuniform electric field [1] in compact installation device, controlled by nuclear (proton) magnetic resonance (NMR) express-analyzer (relaxometer). Installation can be sited directly near oil treating enterprises, sewage treating units, drains, tankers, sea platforms, automobile wash-outs etc. Method includes effect on emulsion of rotating magnetic field B, which

compels charged droplets to move down and so to decrease water concentration. Simultaneously electric field E coagulate small droplets in more large ones, which are also moved down in the area of precipitated water. NMR-relaxometer in this device support control of water concentration [2], dispersion of water droplets [3] in the range 1,5-15 mm, sulphure content [4] and so regulate B, E for maximum effectiveness. Device demonstrate high efficiency, allowing to decrease water content up to 0,2 %.

**References**

1. Kashaev R.S.-H. Patent (Russian) № 1333364 G01N/02. Method for dehydration and desalination of water/oil emulsions and installation for it realization.
2. Kashaev R.S.-H., Temnikov A.N., Idiatullin Z.Sh. Method for water in oil concentration determination // Bulletin of inventions of Russia. – 1997. – №28. – p. 123.
3. Kashaev R.S.-H., Idiatullin Z.Sh., Determination of dispersion characteristics of oil/water emulsions by pulsed field gradient NMR-spectroscopy and NMR-relaxation // 14 EENC98 European Experimental NMR Conference. Abstr. – Bled. Slovenia, 1998. – P.133.
4. Kashaev R.S.-H., Chairullina I.R. Petrochemistry (Russian). – 2009. – V.49, №6. – P. 507-511.

---

The work was submitted to international scientific conference «Wildlife management and preservation of the environment», (France, Paris), 15–22 October, 2010. Came to the editorial office on 02.09.2010.